

Mono Strand Stressing Jack - Front Gripping

Capacity 25 - 30 ton | Stroke 200 mm

Features / Application

- Easy to insert jack over strand in constricted spaces
- Useful for removing slackness in long strands.
- Safety Pressure Relief valve in return line



Mechanical Wedge Lock Arrangement

PSFG Series - P: Planet, S: Single Strand, FG: Front Grippe, 25 Capacity - ton, 200 Stroke - mm

Cap. in (ton)	Cap. in (kN)	Stroke in (mm)	Model	Strand Arrangement in (Inch)	Effective Area in (cm ²)	Oil Cap in (cc)	"A " Closed Height with mechanical Wedge Lock	"A " Closed Height with Hydraulic Wedge Lock	"B" Cylinder OD in (mm)	"C" C Hole in (mm)	"D" Ram Dia in (mm)	"E" Nose Dia in (mm)	Wt. (Approx) in (kg)
25	260	200	PSFG 25-200	0.5-0.6	37.1	742	511	545	110	21	65	45	20
30	308	200	PSFG 30-200	0.5-0.6	44.0	880	511	545	120	21	65	45	25

- Higher capacity and customised solutions on request
- Specifications are subject to change due to continual improvement
- Capacity and stroke Specified are maximum safe limits. As safe practice, use at 80% of rating