

Mono Strand Stressing Jack - Rear Gripping

Capacity 10 - 30 ton | Stroke 500 - 1000 mm

Features / Application

- Long Strokes for Stressing Strand in one pull
- Pulling of Slides, Machines parts & Heavy Fabrication
- Safety Pressure Relief valve in return line



PSFG Series - P: Planet, S: Single Strand, RG: Rear Grippe, 25 Capacity - ton, 200 Stroke - mm

Cap. in (ton)	Cap. in (kN)	Stroke in (mm)	Model	Strand Arrangement in (Inch)	Effective area in (cm ²)	Oil Cap in (cc)	"A" Closed Height (mm)	"B" Cylinder OD in (mm)	"C" C Hole in (mm)	D Ram Dia in (mm)	E Nose Dia in (mm)	Wt (Approx) in (kg)
10	100	500	PSRG 10-500	0.5-0.6	37.7	1885	770	100	20	60	75	34
25	255	750	PSRG 25-750	0.5-0.6	46.3	3475	1046	138	20	80	95	110
30	316	1000	PSRG 30-1000	0.5-0.6	90.3	9035	1280	180	75	120	-	182

- Higher capacity and customised solutions on request
- Specifications are subject to change due to continual improvement
- Capacity and stroke Specified are maximum safe limits. As safe practice, use at 80% of rating